




- Provides Synch mode of operation
- Operates in Polled Mode and DMA mode.
- Support for Big Block and Small Block NAND.
- Support for 1 bit ECC for error correction.
- Supports Wear-Leveling and Bad Block management.
- Support for protected region functionality.
- Modeled after TI Device Driver Architecture for Stream Class Devices that allows for easy porting and customization



Description

Details about the tools and the BIOS version that the driver is compatible with can be found in the system Release Notes.

PRODUCT PREVIEW



Capabilities

The NAND DSP/BIOS device driver adopts a scalable architecture that eases customization/extension

- Isolates H/W and OS Accesses, Easy to maintain & re-target to new platforms
- Can stack custom-functions along control/data-path to realize “driver filters”
- Supports polled as well as DMA mode.
- Supports 1 bit ECC.

For easy and quick reconfiguration of driver, all its statically configurable parameters have been isolated into a single file `nand/dda/dda_nandCfg.c`

The driver is constituted of following sub components:

- NAND DDA – Application facing, OS Specific Adaptation of NAND Device Driver
- NAND DDC – OS Independent part of NAND Driver Core
- NAND LLC – The low-level NAND h/w abstraction module
- System components – PALOS: DSP/BIOS Abstraction

The following table gives a quick overview of the supported API services.


PSP_nandInit()	Create (and initialize) a given NAND driver (instance)
PSP_nandTerminate()	Delete a given NAND driver (instance)
PSP_nandOpen()	Open Instance of the NAND device
PSP_nandClose()	Close Instance of the NAND device
PSP_nandReadSync()	Read data from NAND Instance
PSP_nandWriteSync()	Write data to NAND Instance
PSP_nandIoctl()	Ioctl interface.
PSP_nandErase()	Erases the NAND device
PSP_nandAddDevice ()	Set NAND configuration parameters for a new device ID.



Driver Performance Characteristics

NAND DEVICE DRIVER SUB-COMPONENT	PROGRAM MEMORY (IN BYTES)	DATA MEMORY (IN BYTES)		
		MEMORY TYPE		TOTAL
		INITIALIZED	UN INITIALIZED	
<nand/dda>	5848	775	16896	23519
<nand/ddc>	26496	60	0	26556
<nand/lhc>	2284	407	8	2699
Total	34628	1242	16904	52774

- System Components Total Memory (Code & Data): 52774 Bytes



- Throughput of NAND driver in DMA mode

Note: The Driver Performance Characteristics can be included once testing is done on DM6437/C6424 SoC. For generating performance figures of NAND driver in other modes please refer the top-level user guide for usage of SoC Analyzer.

PRODUCT PREVIEW



References

[1] NAND Module Hardware Specifications

[2] NAND Device Driver Documentation

Glossary

LLC	TI Terminology, Low Level Controller
DDA	TI Terminology, Device Driver Adapter to OS
DDC	TI Terminology, Device Driver Core that is OS independent

PRODUCT PREVIEW

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Copyright © 2007 Texas Instruments Incorporated. All rights reserved.

Information in this document is subject to change without notice. Texas Instruments may have pending patent applications, trademarks, copyrights, or other intellectual property rights covering matter in this document. The furnishing of this documents is given for usage with Texas Instruments products only and does not give you any license to the intellectual property that might be contained within this document. Texas Instruments makes no implied or expressed warranties in this document and is not responsible for the products based from this document. This information applies to a product under development. Its characteristics and specifications are subject to change without notice. Texas Instruments assumes no obligation regarding future manufacturing unless otherwise agreed to in writing.