




- Multi-instantiable and re-entrant safe driver
- Provides Synch mode of operation.
- Programmed serial bit of stream between 2 to 16 bit.
- Can be configured in Three and Four pin mode of operation.
- Data transfer rate can be programmed for different value.



PRODUCT PREVIEW

PROS SPI DEVICE DRIVER

Capabilities

The SPI BIOS device driver adopts a scalable architecture that eases customization/extension

- Isolates H/W and OS Accesses, Easy to maintain & re-target to new platforms
- Supports Multiple Instances

The driver is constituted of following sub components:

- SPI DDA –OS Specific Adaptation of SPI Device Driver
- SPI DDC – OS Independent part of SPI Driver Core. This also includes CSLR.
- System components – PALOS: BIOS Abstraction

The following table gives a quick overview of the supported API services. For help on interfaces refer to the SPI Driver Help File:


GIO_create	Creates the communication channel (Tx/Rx) for the data transfer by setting up SPI channel parameters. It calls PSP_spiCreate () driver core function to achieve this.
GIO_Delete	Delete the channel object and freeing up channel resources. It calls PSP_spiDelete () driver core function to achieve this.
GIO_Submit	Submit IO request packet to the SPI driver. The submit command may be read/write/flush/abort. It calls PSP_spiSubmit () for input/output command or PSP_spiAbort () for abort/flush command.
GIO_control	This is used to perform input output control (IOCTL) on the SPI driver on the fly. It calls PSP_spioctl () to achieve this.



Driver Performance Characteristics

SPI DEVICE DRIVER SUB-COMPONENT	PROGRAM MEMORY (IN BYTES)	DATA MEMORY (IN BYTES)		
		MEMORY TYPE		TOTAL
		INITIALIZED	UN INITIALIZED	
<SPI/IOM>	1632	128	104	1864
<SPI/DDC>	7584	268	296	8148
Total	9216	396	400	10012

- System Components Total Memory (Code & Data):
Code = 9056 Bytes.
Data = 792 Bytes.
Total = 9848 Bytes



PRODUCT PREVIEW

Test Setup Information	Trial No.	Polled			Interrupt		
		Bits/Sec	Bytes Transferred	Duration	Bits/Sec	Bytes Transferred	Duration
	1	6506.67	48800	60	13014.40	97608	60
	2	6506.67	48800	60	13014.40	97608	60
API Interface : GIO_Submit	3	6506.67	48800	60	13013.33	97600	60
	4	6506.67	48800	60	13013.33	97600	60
	5	6506.67	48800	60	13014.40	97608	60
Comments:							
SPI connected with ATMEL64025256A EEPROM							
SPI Bus Clock Rate : 3 Mhz							

Driver Profiling Characteristics

PROS SPI DEVICE DRIVER

Polled Mode								
API Profiled	Trial-1	Trial-2	Trial-3	Trial-4	Trial-5	Average (usec)	Maximum (usec)	Minimum (usec)
DEV_createDevice	2.00	2.00	2.00	3.00	2.00	2.20	3.00	2.00
GIO_create	7.00	8.00	7.00	7.00	8.00	7.40	8.00	7.00
GIO_write	11.00	12.00	11.00	12.00	12.00	11.60	12.00	11.00
GIO_read	13.00	12.00	11.00	12.00	12.00	12.00	13.00	11.00
GIO_delete	12.00	12.00	12.00	11.00	12.00	11.80	12.00	11.00
DEV_deleteDevice	5.00	3.00	5.00	6.00	5.00	4.80	6.00	3.00
Interrupt Mode								
API Profiled	Trial-1	Trial-2	Trial-3	Trial-4	Trial-5	Average (usec)	Maximum (usec)	Minimum (usec)
DEV_createDevice	3.00	3.00	2.00	3.00	4.00	3.00	4.00	2.00
GIO_create	7.00	8.00	7.00	8.00	8.00	7.60	8.00	7.00
GIO_write	12.00	12.00	11.00	9.00	9.00	10.60	12.00	9.00
GIO_read	12.00	12.00	9.00	12.00	9.00	10.80	12.00	9.00
GIO_delete	12.00	15.00	9.00	12.00	12.00	12.00	15.00	9.00
DEV_deleteDevice	5.00	2.00	2.00	5.00	5.00	3.80	5.00	2.00

1 sec 26984800 ticks
 1 tick 3.70579E-05 usecs

PSP_PSP_SPI_IOCTL_SET_LOOPBACK_IOCTL_ENABLE_DLB Was used to profile IOCTL

References

- [1] SPI Functional Specifications
- [2] BIOS Documentation from TI
- [3] SPI Device Driver Documentation

Glossary

IOM TI Terminology, Input / Output mini Driver.
 DDC TI Terminology, Device Driver Core that is OS independent
 HAL Hardware Abstraction Layer

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Copyright © 2005 Texas Instruments Incorporated. All rights reserved.

Information in this document is subject to change without notice. Texas Instruments may have pending patent applications, trademarks, copyrights, or other intellectual property rights covering matter in this document. The furnishing of this documents is given for usage with Texas Instruments products only and does not give you any license to the intellectual property that might be contained within this document. Texas Instruments makes no implied or expressed warranties in this document and is not responsible for the products based from this document. This information applies to a product under development. Its characteristics and specifications are subject to change without notice. Texas Instruments assumes no obligation regarding future manufacturing unless otherwise agreed to in writing.