




- Middle layer of the driver conforms to IO Mini driver model defined by the DSP/BIOS DDK (Device Driver Development Kit) Framework.
- Supports EDMA and interrupt modes of operation (Interrupt mode not tested)
- Supports receive and transmit in I2S mode and transmit in DIT mode



Description

- Details of tools used and versions are available in release notes



Capabilities

The following table gives a quick overview of the supported API provided by the GIO layer to interact with the driver

| GIO API called by application | mini-driver API called | Description |
|---|--|--|
| GIO_create (name, Int mode, Int *status, Ptr chanParams, GIO_Attrs *attrs); | static Int mcasep_mdCreateChan (Ptr *chanp, Ptr devp, String name, Int mode, Ptr chanParams, IOM_TiomCallback cbFxn, Ptr cbArg); | This assigns one of the device channels to be used for the operation (rcv/xmt). It hooks up the necessary ISRs and configures the associated eDMA channel. |
| GIO_Delete (GIO_Handle gioChan); | static Int mcasep_mdDeleteChan(Ptr chanp); | Frees up resources held by channel. |
| GIO_submit (gioChan, IOM_READ, bufp, psize, appCallback); | static Int mcasep_mdSubmitChan(Ptr chanp, IOM_Packet *packet); | Submits a read packet to configure the McASP receive section with. |
| GIO_submit (gioChan, IOM_WRITE, bufp, psize, appCallback); | static Int mcasep_mdSubmitChan(Ptr chanp, IOM_Packet *packet); | Submits a write packet to configure the McASP transmit section with. |
| GIO_Flush(gioChan); | static Int mcasep_mdControlChan(Ptr chanp, Uint16 cmd, Ptr args); | Drains all existing packets for this channel. This call also prevents stalls submission of packets to the channel |
| GIO_Abort(gioChan); | static Int mcasep_mdControlChan(Ptr chanp, Uint16 cmd, Ptr args); | This call aborts all packets submitted to the channel and places the corresponding state machine in reset. |
| GIO_Control(gioChan, cmd, args); | static Int mcasep_mdControlChan(Ptr chanp, Uint16 cmd, Ptr args); | This submits other control commands to the mini-driver. |

PRODUCT PREVIEW



Driver Performance Characteristics

Release Mode:

| MCASP DEVICE DRIVER SUB-COMPONENT | PROGRAM MEMORY (IN BYTES) | DATA MEMORY (IN BYTES) | | |
|--------------------------------------|---------------------------------|---------------------------|----------------|--------------|
| | | MEMORY TYPE | | TOTAL |
| | | INITIALIZED | UN INITIALIZED | |
| dda | 2284 | 40 | 156 | 2480 |
| ddc | 24212 | 152 | 4232 | 28596 |
| llc | 9500 | 0 | 660 | 9500 |
| Total | 35996 | 192 | 4388 | 40576 |

- System Components Total Memory (Code & Data): **40576** Bytes

Note: The Driver Performance Characteristics can be included once testing is done on DM648/C6452 SOC.

Driver Profiling Characteristics

| SIO | | | | | | |
|--------------------|---------|---------|---------|-----------------|-----------------|-----------------|
| API Profiled | Trial-1 | Trial-2 | Trial-3 | Average (usecs) | Maximum (usecs) | Minimum (usecs) |
| SIO_create - Tx | 2301263 | 2301263 | 2301260 | 2301262 | 2301263 | 2301260 |
| SIO_create - Rx | 57 | 56 | 57 | 57 | 57 | 56 |
| SIO_Submit - Write | 1 | 1 | 1 | 1 | 1 | 1 |
| SIO_Submit- Read | 1 | 1 | 1 | 1 | 1 | 1 |
| SIO_Delete - Tx | 20 | 20 | 20 | 20 | 20 | 20 |
| SIO_Delete- Rx | 39 | 39 | 39 | 39 | 39 | 39 |

Note: Due to the initialization of codec related steps GIO_create - Tx is taking extremely large time.

| GIO | | | | | | |
|--------------------|---------|---------|---------|-----------------|-----------------|-----------------|
| API Profiled | Trial-1 | Trial-2 | Trial-3 | Average (usecs) | Maximum (usecs) | Minimum (usecs) |
| GIO_create - Tx | 2301265 | 2301265 | 2301264 | 2301265 | 2301265 | 2301264 |
| GIO_create - Rx | 55 | 55 | 55 | 55 | 55 | 55 |
| GIO_Submit - Write | 23 | 22 | 22 | 22 | 22 | 22 |
| GIO_Submit- Read | 14 | 13 | 13 | 13 | 14 | 13 |
| GIO_Delete - Tx | 20 | 30 | 29 | 26 | 30 | 20 |
| GIO_Delete- Rx | 38 | 82 | 84 | 68 | 84 | 38 |

Note: Due to the initialization of codec related steps GIO_create - Tx is taking extremely large time.

PRODUCT PREVIEW



Driver Performance Characteristics

AUDIO_WRITE

| Test Setup Information | Sampling Rate in Hz | Word Length in bits | No. of channels/sample | DMA Mode | | |
|------------------------|---------------------|---------------------|------------------------|------------------|----------------------|-----------------|
| | | | | No. of bytes/Sec | Buffer Size in Bytes | Duration in Sec |
| ARM Frequency = 26 MHZ | 8000 | 32 | 1 | 32931 | 15360 | 50 |
| | 12600 | 32 | 1 | 51916 | 15360 | 50 |
| | 44100 | 32 | 1 | 179896 | 15360 | 50 |
| | 48000 | 32 | 1 | 195788 | 15360 | 50 |
| | 96000 | 32 | 1 | 391230 | 15360 | 50 |

AUDIO_READ

| Test Setup Information | Sampling Rate in Hz | Word Length in bits | No. of channels/sample | DMA Mode | | |
|------------------------|---------------------|---------------------|------------------------|------------------|-------------------|-----------------|
| | | | | No. of bytes/Sec | Buffer Size in KB | Duration in Sec |
| ARM Frequency = 26 MHZ | 8000 | 32 | 1 | 32931 | 15360 | 50 |
| | 12600 | 32 | 1 | 51609 | 15360 | 50 |
| | 44100 | 32 | 1 | 179180 | 15360 | 50 |
| | 48000 | 32 | 1 | 195779 | 15360 | 50 |
| | 96000 | 32 | 1 | 391249 | 15360 | 50 |

References

- [1] DSP/BIOS Driver Developer's guide
- [2] McASP Programmer's Reference Guide

Glossary

| | |
|-------|---|
| IOM | TI Terminology, Input/Output Mini Driver. |
| DDC | TI Terminology, Device Driver Core that is OS independent |
| CSL | Chip Support Library |
| GIO | Generic I/O Module |
| McASP | Multi-channel Audio Serial Port |
| I2S | Inter-Integrated Sound protocol |
| DIT | Digital Audio Interface Transmission |
| IOM | Input/Output Module |
| EDMA | Enhanced Direct Memory Access |

PRODUCT PREVIEW



PRODUCT PREVIEW

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Copyright © 2007 Texas Instruments Incorporated. All rights reserved.

Information in this document is subject to change without notice. Texas Instruments may have pending patent applications, trademarks, copyrights, or other intellectual property rights covering matter in this document. The furnishing of this documents is given for usage with Texas Instruments products only and does not give you any license to the intellectual property that might be contained within this document. Texas Instruments makes no implied or expressed warranties in this document and is not responsible for the products based from this document. This information applies to a product under development. Its characteristics and specifications are subject to change without notice. Texas Instruments assumes no obligation regarding future manufacturing unless otherwise agreed to in writing.