




- Single Instance and re-entrant safe driver
- Operates in INTERRUPT mode only.
- Support individual channels for CCDC.
- Supports flipping of multiple frame buffers for seamless capture from CCDC.
- Easy to maintain & re-target to new platforms.



## Description

Details about the tools and the BIOS version that the driver is compatible with can be found in the system Release Notes.

PRODUCT PREVIEW



## Capabilities

The VPFE BIOS device driver adopts a scalable architecture that eases customization/extension

- Isolates H/W and OS Accesses
- Easy to maintain & re-target to new platforms.

The driver is constituted of following sub components:

- VPFE IOM –OS Specific Adaptation of VPFE Device Driver
- VPFE DDC – OS Independent part of VPFE Driver Core. This also includes LLC.
- System components – BIOS: BIOS Abstraction.

The following table gives a quick overview of the supported API services. For help on interfaces refer to the VPFE Driver Help File:

GIO_create	Call PSP_VPFECreate, Creates the channel for the data transfer by setting up VPFE hardware params
GIO_Delete	Call PSP_VPFEClose, which will Delete a given VPFE driver (channel).
GIO_submit	Call the PSP_VPFESubmitRequest for Queuing and Dequeuing the Frame buffers for CCD and other VPFE modules.
GIO_control	Call PSP_VPFElctl that will do lctl interface. lctl's Supported are: Refer User guide document



### Driver Performance Characteristics

VPFE DEVICE DRIVER SUB-COMPONENT	PROGRAM MEMORY (IN BYTES)	DATA MEMORY (IN BYTES)		
		MEMORY TYPE		TOTAL
		INITIALIZED	UN INITIALIZED	
<VPFE/IOM>	3392	132	116	3640
<VPFE/DDC>	8768	99	154	9021
<VPFE/LLC>	3168	0	4	3172
<b>Total</b>	<b>15328</b>	<b>231</b>	<b>274</b>	<b>15833</b>

- VPFE System Components Total Memory (Code & Data): **15833** Bytes

**Note:** The Driver Performance Characteristics can be included once testing is done on DM6437 SOC.

PRODUCT PREVIEW



PRODUCT PREVIEW

- Latency graph for VPFE/VPBE driver



## References

[1] VPSS Module Hardware Specifications

[2] BIOS Documentation from TI

[3] VPFE Device Driver Documentation

## Glossary

IOM	TI Terminology, Input/Output Mini Driver.
DDA	TI Terminology, Device Driver Adaptation that is OS dependent
DDC	TI Terminology, Device Driver Core that is OS independent
LLC	TI Terminology, Device Driver Core that is hardware dependent

## **IMPORTANT NOTICE**

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

**Copyright © 2007 Texas Instruments Incorporated. All rights reserved.**

Information in this document is subject to change without notice. Texas Instruments may have pending patent applications, trademarks, copyrights, or other intellectual property rights covering matter in this document. The furnishing of this documents is given for usage with Texas Instruments products only and does not give you any license to the intellectual property that might be contained within this document. Texas Instruments makes no implied or expressed warranties in this document and is not responsible for the products based from this document. This information applies to a product under development. Its characteristics and specifications are subject to change without notice. Texas Instruments assumes no obligation regarding future manufacturing unless otherwise agreed to in writing.