

HEVC/H.265 Main Profile Encoder (v02.00.00) on TMS320C6678 Platform

FEATURES

- Supports encoding of HEVC Main, Main Still profile bitstreams up to level 5.0
- Supports arbitrary resolutions from 128x96 up to 4096x2160
- Supports standard resolutions which are multiple of 2
- Supports YUV 4:2:0 Planar Chroma format
- Supports encoding progressive content
- Supports SEI and VUI parameters encoding.
- Supports I, P and B frame encoding
- Supports CTU sizes 64x64, 32x32, 16x16
- Supports RDO based encoding
- Supports multiple slice, multiple tile encoding
- Supports multiple reference frame encoding
- Supports encoding of streams with Wave front parallel processing feature
- Supports Low delay and Random access configurations
- Supports encoding of streams with scaling matrices
- Supports Deblocking and SAO features
- Supports encoding with dependent slices
- Supports insertion of IDR frame at random point with force frame control
- Supports constrained intra prediction
- Supports AIR(Adaptive Intra Refresh) with cyclic intra macroblocks
- Supports user controllable quantization parameter range, initial quantization parameter, HRD buffer size.
- Supports separate Cb and Cr quantization parameter control
- Supports user controlled Quarter pel & Half pel MV accuracy
- Supports user controlled in loop filter & SAO features which can be enabled/disabled at picture offset.
- Supports transform skip and trans quant bypass mode
- Supports to control the balance between encoding speed and quality by using user definable encoding preset option
- Supports call back API functions at CTU row level decoding
- Supports change of frame rate, bitrate dynamically
- Supports user controlled IDR frequency control
- Supports user configurable group of pictures (GOP) length and different GOP structures.
- Supports capability to generate only header
- Encoder library validated on DSPC-8681 and DSPC-8682 card based on TMS320C6678 platform
- The other explicit features that TI's HEVC Main Profile Encoder supports are
 - eXpressDSP Digital Media (XDM IVIDENC2) interface compliant
 - TI's Multicore interface(IVIDMC3) compliant
 - Independent of any operating system (DSP/BIOS, Linux etc)
 - Cache aware Encoder library

DESCRIPTION

HEVC/H265 is video compression standard from ITU-T Video Coding Experts Group and the ISO/IEC Moving Pictures Experts Group successor to H264/MPEG4 AVC. Higher Data compression ratio is achieved compared to H.264/MPEG-4 AVC at the same level of video quality. It can alternatively be used to provide substantially improved video quality at the same bit rate. It can support 8K UHD and resolutions up to 8192x4320

This project is developed and validated on DSPC- 8681 and DSPC-8682 cards based on TMS320C6678 platform using Code Composer Studio version 5.5.0.00077 and code generation tools version 7.4.6.

PRODUCT PREVIEW



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Performance and Memory Summary

This section describes the performance and memory usage of the HEVC Main profile Encoder tested on DSPC-8681 and DSPC-8682 cards based on TMS320C6678 platform.

Table 1 Configuration Table

CONFIGURATION	ID
HEVC Main Profile, IBB, Random Access, Multi chip(6 Chips)	H265MP_ENC_001
HEVC Main Profile, IBB, Random Access, Multi chip(3 Chips)	H265MP_ENC_002
HEVC Main Profile, IBB, Random Access, Multi core(2 Chips)	H265MP_ENC_003
HEVC Main Profile, IPP, Low Delay, Multi Chip(2 Chips)	H265MP_ENC_004
HEVC Main Profile, IPP, Low Delay, Multi Chip(19 Cores)	H265MP_ENC_005
HEVC Main Profile, IBB, Random Access, Multi core(1 Chip)	H265MP_ENC_006
HEVC Main Profile, IBB, Random Access, Multi core(8 Chips)	H265MP_ENC_007

Table 2 Cycles Information - Profiled on DSPC-8681 card with Code Generation Tools Version 7.4.6

CONFIGURATION ID	PERFORMANCE STATISTICS (MEGA CYCLES PER SECOND) ⁽¹⁾		
	TEST DESCRIPTION	AVERAGE ⁽²⁾	PEAK ⁽³⁾
H265MP_ENC_001	Airshow_p1920x1080_420p.yuv, YUV420, Random Access, IBB @ 10Mbps @ 60 frames per second	1139	1165
H265MP_ENC_002	Airshow_p1920x1080_420p.yuv, YUV420, Random Access, IBB @ 5Mbps @ 30 frames per second	1086	1108
	Airshow_p1280x720_420p.yuv, YUV420, Random Access, IBB @ 6Mbps @ 60 frames per second	1122	1140
H265MP_ENC_003	Airshow_p1280x720_420p.yuv, YUV420, Random Access, IBB @ 3Mbps @ 30 frames per second	752	767
H265MP_ENC_004	Shyam_p1920x1080_420p.yuv, YUV420, Low Delay, IPP @ 2Mbps @ 60 frames per second	1242	1247
H265MP_ENC_005	Shyam_p1920x1080_420p.yuv, YUV420, Low Delay, IPP @ 4Mbps @ 60 frames per second	1246	1248
H265MP_ENC_006	Airshow_p720x480_420p.yuv, YUV420, Random Access, IBB @ 2Mbps @ 60 frames per second	973	990
H265MP_ENC_007	Airshow_p3840x2160_420p.yuv, YUV420, Random Access, IBB @ 16Mbps @ 30 frames per second	1156	1186

(1) Measured with C66x DSP 1250MHz clock, DDR3 1333MHZ clock, Program memory in SL2 memory, I/O buffers in external memory and stack in internal L2 memory with cache configurations: 32KB L1P Program cache, 32KB L1D Data cache and 64KB L2 cache. Performance is measured using MCSDK Video version 2.2.0.42 to make sure system overheads are included. There could be a variation of approximately 2-3% in the values.

(2) Average cycles are calculated as maximum of moving average for frames in 1 sec, multiplied with frame rate to get per second Mhz.

(3) Peak cycles are calculated as maximum of moving average for frames in 0.5 sec, multiplied with frame rate to get per second Mhz.

Table 3 Memory Statistics of HEVC Encoder with Code Generation Tools Version 7.4.6

CONFIGURATION ID	MEMORY STATISTICS ⁽¹⁾⁽²⁾					
	PROGRAM MEMORY ⁽⁴⁾	DATA MEMORY ⁽³⁾				TOTAL
		PERSISTENT	CONSTANT	SHARED	SCRATCH	
H265MP_ENC_001	953	19	27	35264	0	36263
H265MP_ENC_002	953	19	27	42795	0	43794
H265MP_ENC_003	953	19	27	27999	0	28998
H265MP_ENC_004	953	19	27	49297	0	50296
H265MP_ENC_005	953	19	27	44346	0	45345
H265MP_ENC_006	953	19	27	17389	0	18388
H265MP_ENC_007	953	19	27	111157	0	112156

- (1) All these memory requirements are for HEVC Main Profile Encoder library only. They do not include any memory requirements from application side. Stack, heap and code requirements for application are extra.
- (2) All memory requirements are expressed in kilobytes (1K bytes = 1024 bytes).
- (3) Program code is stored in SL2 memory.

Table 4 Internal Data Memory Split-up

CONFIGURATION ID	DATA MEMORY – INTERNAL ^{(1) (2)}					
	LOCAL L2				SHARED L2 ⁽³⁾	TOTAL
	CONSTANTS	PERSISTENT	SCRATCH	STACK		
H265MP_ENC_001 H265MP_ENC_002 H265MP_ENC_003 H265MP_ENC_004 H265MP_ENC_005 H265MP_ENC_006 H265MP_ENC_007	0	0	283	8	1454	1745

- (1) Internal memory requirements are for each individual core.
- (2) All memory requirements are expressed in kilobytes (1K bytes = 1024 bytes).
- (3) Encoder tables are placed in Shared L2 (MSMC) memory.

Table 5 Cache/SRAM configuration ⁽¹⁾

NAME	AVAILABLE	CACHE	SRAM
L1P (Program Memory)	32KB	32KB	0KB
L1D(Data Memory)	32KB	32KB	0KB
L2	512KB	64KB	448KB

- (1) All above mentioned numbers are for all configurations.

Table 6 EDMA Configuration ^{(1) (5)(6)}

TC Q	TC 0	TC 1	TC 2	TC 3	TOTAL	MAXIMUM ⁽³⁾
Usage	R/W to DDR/L2	-	-	-	-	-
Priority ⁽²⁾	0	-	-	-	-	-
EDMA Channels	8	-	-	-	8 ⁽⁴⁾	64
QDMA Channels	-	-	-	-	0 ⁽⁴⁾	8
Num PARAMS	48 ⁽⁴⁾	-	-	-	48 ⁽⁴⁾	512

- (1) All above mentioned numbers are for all configurations (H265MP_ENC_001, H265MP_ENC_002, H265MP_ENC_003, H265MP_ENC_004, H265MP_ENC_005, H265MP_ENC_006 and H265MP_ENC_007).
- (2) Lesser number corresponds to higher TC priority. Default priority is TC0 > TC1 > TC2 > TC3. When different TC's have same priority, the arbitration order is TC0 > TC1 > TC2 > TC3.
- (3) Max corresponds to the maximum number of EDMA/QDMA channels or maximum number of PARAMS available on the chip for a channel controller. It does NOT indicate the maximum number requested by the codec.
- (4) Same EDMA channel is used to copy data to DDR and to L2 memory at different instances.
- (5) Above configuration table specifies EDMA hardware usage for each core in multicore/multichip scenario.
- (6) Core 0,1,2,3 uses EDMA CC1 and Core 4,5,6,7 uses EDMA CC2.

Notes

- I/O buffers:
 - Input buffer size = 3060 K-bytes (for 1920x1088 resolution, YUV420)
 - Input buffer size = 12150 K-bytes (for 3840x2160 resolution, YUV420)
 - Output buffer size = 3584 K-bytes

References

- ISO/IEC 23008-2:2013 Infrastructure of audiovisual services - Coding of moving video: High efficiency video encoding.
- eXpressDSP Algorithm Interoperability Standard (TMS320 Algorithm Interface Standard).
- HEVC Main Profile Encoder on TMS320C6678 Platform User's Guide.

Glossary

Term	Description
Constants	Elements that go into .const memory section
Scratch	Memory space that can be reused across different instances of the algorithm
Shared	Sum of Constants and Scratch
Instance	Persistent-memory that contains persistent information - allocated for each instance of the algorithm

Acronyms

Acronym	Description
HEVC	High Efficiency Video Codec
DMA	Direct Memory Access
ISO	International organization for standardization
EVM	Evaluation Module
AVC	Advanced Video Codec
XDAIS	eXpressDSP Algorithm Interface Standard
XDM	eXpressDSP Digital Media

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio www.ti.com/audio
Amplifiers amplifier.ti.com
Data Converters dataconverter.ti.com
DLP® Products www.dlp.com
DSP dsp.ti.com
Clocks and Timers
Interface interface.ti.com
Logic logic.ti.com
Power Mgmt power.ti.com
Microcontrollers microcontroller.ti.com
RFID www.ti-rfid.com
OMAP Applications Processors
Wireless Connectivity

Applications

Automotive & Transportation www.ti.com/automotive
Communications & Telecom www.ti.com/communications
Computers & Peripherals www.ti.com/computers
Consumer Electronics www.ti.com/consumer-apps
Energy and Lighting www.ti.com/energyapps
www.ti.com/clocks Industrial www.ti.com/industrial
Medical www.ti.com/medical
Security www.ti.com/security
Space, Avionics & Defense www.ti.com/space-avionics-defense
Video & Imaging www.ti.com/video

www.ti.com/omap **TI E2E Community** e2e.ti.com
www.ti.com/wirelessconnectivity

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright© 2014, Texas Instruments Incorporated